



DHN-LVWES05-G1

Rechargeable Lithium Iron Battery

The DHN-LVWES series product is a low-voltage energy storage battery designed to provide efficient and reliable energy storage solutions for households, businesses, and specific occasions. Adopting top tier brand lithium iron phosphate battery cells, with high safety, stability, energy density, and long cycle life. Built in efficient intelligent battery management system(BMS), comprehensively monitoring and controlling the battery energy storage system to ensure its safe, stable and high-performance operation.



Safe

- A-grade lithium iron phosphate battery with high safety performance.
- Intelligent BMS with multiple safety functions, making it safer to use.
- Fire Protection System: Optional pre-setting fire extinguisher.



Long Life-time

- Cycle life of over 6000 cycles (70% SOH).
- High parallel balancing current to ensure battery consistency.



Convenient & Smart

- Bluetooth/WiFi function, support real time monitor and remote software upgrade by APP
- Support Bluetooth/WiFi inverter protocol configuration function, quickly set-up and easy to operate
- Automatic networking of battery modules, easy to maintain.



Flexible

- Small size, high power density, Suitable for installation scenarios with limited space.
- The unique dual-positive and dual-negative terminal design allows direct stacking and parallel connection without the need for additional busbars, saving costs and installation space.
- Match with mainstream low-voltage energy storage inverters.




One-stop Service

- DAH Solar provide integrated system configuration services from PV to energy storage.

TECHNICAL PARAMETER

System Application



Technical Data

| Model | DHN-LVWES05-G1 |
|-------|----------------|
|-------|----------------|

Main Parameter

| | |
|--|---------------------------------------|
| Battery Type | LiFePO4 |
| Battery Rated Energy (kWh) | 5.12 |
| Battery Rated Capacity (Ah) | 100 |
| Scalability | Parallel connection of up to 16 units |
| Nominal Voltage (V) | 51.2 |
| Operating Voltage(V) | 43.2~58.4 |
| Charge/Discharge Current (A)–Recommend | 50 |
| Charge/Discharge Current (A)–Max. | 100 |

Other Parameter

| | |
|--------------------------------------|---|
| Recommend Depth of Discharge(%) | ≤90 |
| System Dimension (W/H/D, mm) | 480×500×155 |
| System Weight (kg) | 47 |
| Master LED Indicator | 6LED (SOC:16.6%~100%), 3LED (ON/OFF,RUN,ALARM) |
| IP Rating of Enclosure | IP20 |
| Operating Temperature(°C) | Charge:0~+60/Discharge:−20~+60 |
| Storage Temperature(°C) | 0~+35 |
| Cycle Life (25±2°C,0.5C/0.5C,70%EOL) | ≥6000 |
| Installation | Wall–Mounted/Floor–Mounted |
| Fire Prevention System | Prefabricated whole fluorine ketone fire extinguishing device (optional) |
| Communication Methods | CAN2.0/RS485 |
| Warranty Period (years) | 5 |
| Certification | IEC62619–CB,CE,UN38.3 |
| Compatible Inverters | SA/ICTRON/SE/DEYE/SOLIS/GOODWE/GROWATT/LUXPOWERTEK/SENERGY/SRD/SOLPLANET etc. |